

### ABOUT

- Flexible LED Neon with sideways (left to right) bending profile.
- Various colour temperature and coloured options available.
- IP 67 waterproof and yellow-resistant.
- Cutting intervals of 20 to 25mm, which is the smallest cut interval on the market.
- Made to order to custom lengths.
- Can be paired with our extrusions: AE 1212, AE1510DW, AE1510SW. This can be used in conjunction with our EL1212F for areas with tricky curves to navigate.

### LED Quantity & Rated Power

168LEDs/M - 9.6W/M

### Maximum Length

10M

### Size

12mm X 12mm

### Input Voltage

24V

### Colour Temperature

3000K / 4000K / 5000K

### PCB Width

10mm

### Beam Angle Selection

120°

### Cutting Increment

25mm

### Luminous Flux

1200 ~ 1330 lm/M

### LED Type

SMD2835

### Colour Rendering

Index 90+


### IP Rating

65


### Warranty

2 Years


## BEND MANUAL




Lighting Profile





Bending Direction



Bend Radius



Bend Radius



Aluminium Profile

## PRODUCT ORDER CODE

[ E.G. EL1212S - 12V - 3000K - 120LEDs/M 9.6W/M - NON-DIM ]

CODE

EL1212S

INPUT VOLT

24V

CCT

3000K

4000K

5000K

LED QUANTITY

168LEDs/M  
9.6W/M

DIMMING

DIM

NON-DIM