



SPECIFICATION SHEET

AUSTRALIA / INTERNATIONAL

180LEDs/M
 CRI 90 + / 1200~1330lm/M



ABOUT

- Flexible LED Neon with up and down bending profile.
- Various colour temperature and coloured options available.
- IP 67 waterproof and yellow-resistant.
- Cutting intervals of 20 to 25mm, which is the smallest cut interval on the market.
- Made to order to custom lengths.
- Can be paired with our extrusions: AE 1710. One of our most versatile models, this model is particularly suitable for joinery, ceilings or walls that impact.

LED Quantity & Rated Power

180LEDs/M - 12.6W/M

Maximum Length

10M

Colour Temperature

3000K / 4000K / 5000K

Cutting Increment

25mm

Colour Rendering

Index 90+

Size

15mm X 10mm

PCB Width

10mm

Luminous Flux

1200 ~ 1330 lm/M

IP Rating

65

Input Voltage

24V

Beam Angle Selection

120°


LED Type

SMD2835


Warranty

2 Years


BEND MANUAL




Lighting Profile




Bending Direction



Bend Radius



Bend Radius



Aluminium Profile (Extrusion: AE1710)



End Cap (With/Without Hole)



Aluminium Clip

PRODUCT ORDER CODE

[E.G. EL1510F - 24V - 3000K - 180LEDs/M 12.6W/M - NON-DIM]

