

SPECIFICATION SHEET

AUSTRALIA / INTERNATIONAL

CATEGORIES LED STRIP LIGHT SL24120D5

24 Voltage / 120LEDs/M - 9.6W/M CRI 90 + / 980 ~ 1050 lm



| 10000111 | | | | | | | | | | | | | | | | | |
|----------|----------|--|---|--|--|--|---|-----|----------|--|--|--|--|--|---|-------|---------------|
| | | | | | | | | \$ |) E= | | | | | | | | I 5MM 1 |
| 2.17 | <u> </u> | | n | | | | (|) | <u>}</u> | | | | | | п | n | - |
| | | | | | | | | 100 | | | | | | | | | |

ABOUT

- Flexible LED strip with close pitch of 120 LEDs per metre for reduced spotting effect.
- Available in reels up to 10 metres with cutting intervals of 9mm, which is the smallest cut interval on the market for 24V.
- Even illumination with no dark areas at the ends.
- Can be paired with a variety of extrusion profiles to suit any interior scheme.
- Ideal for high-end application C-TICK and SAA Approved.

LED Quantity

120 leds/m

Colour Temperature 3000K / 4000K

Standard Length

10 M

Input Voltage

24V

IP Rating

20

Size 1.45mm X 5mm

Luminous Flux

980~1050 lm/M

Rated Power

9.6 W/M

Beam Angle Selection

120°

Dimming

Optional

LED Type

SMD2835

Colour Rendering

Index 90+

Warranty

2 Years