

ABOUT


- Flexible LED Neon with up and down bending profile.
- Various colour temperature and coloured options available.
- IP 67 waterproof and yellow-resistant.
- Cutting intervals of 20 to 25mm, which is the smallest cut interval on the market.
- Made to order to custom lengths.
- Can be paired with our extrusions: AE1212, AE1212DW (Flexi), AE1212SW (Flexi). One of our most versatile models, suitable for various applications.

LED Quantity & Rated Power


120LEDs/M-9.6W/M / 168LEDs/M-9.6W/M / 168LEDs/M-12W/M

Maximum Length	Size	Input Voltage
10M	12mm X 12mm	12V / 24V
Colour Temperature	PCB Width	Beam Angle Selection
2700K / 3000K / 4000K / 5000K	8mm	120°
Cutting Increment	Luminous Flux	LED Type
25mm	1200 ~ 1330 lm/M	SMD2835
Colour Rendering	IP Rating	Warranty
Index 90+	65	2 Years


BEND MANUAL




Lighting Profile




Bending Direction




Bend Radius



Bend Radius



Aluminium Profile



Flexible Aluminium Profile

PRODUCT ORDER CODE

[E.G. EL1212F - 12V - 3000K - 120LEDs/M 9.6W/M - NON-DIM]

